

Extra Clean

Professional Aerosol Foaming Cleaner



- Industrial strength, triple power, deep cleaning foam formula that penetrates, lifts and emulsifies dirt, grease, oil, grime, stains and more.
- A convenient, easy to use product. Simply spray on and wipe off.
- Foaming cleaner clings to vertical surfaces and penetrates the toughest stains.
- Fresh citrus scent deodorizes as it cleans.
- No rinse formula adds to ease of use.
- Cleans almost anything and is safer to use than other industrial aerosol cleaners.



Cleans almost ANYTHING!

Racecars....Walls....Tools
Parts.....Workbenches
Cabinets.....CRT screens
Stainless Steel.....Plastic
Helmets.....Ceramic tile
Rubber.....Laminates

**V.O.C. compliant with
all U.S Federal and
State regulations.**

"The Surface Cleaning Specialists"

Saric Solutions, Inc.
PO Box 1807
Fuquay-Varina, NC 27526-1807
Phone: 866.552.8830
Email: info@saricsolutions.com
www.saricsolutions.com

Product Specifications

Color: White Foam	Rinse Free: Yes
Odor: Citrus	Flash Point: -156 °F
Specific Gravity: 0.96	Biodegradable: Yes
Evaporation: Unknown	Solubility: Complete
Foam: No Run, Clings	Can size: 20oz.
Abrasives: None	Carton Pack: 12
Phosphates: None	Keep from Freezing
Emulsifier: Excellent	All Information subject to change.

***Don't Get Black Flagged,
Clean Green and Win!***

Material Safety Data Sheet

PRODUCT NAME: EXTRA CLEEN

HMS CODES: H F R P

PRODUCT CODE: B-00044

1 2 0

DISTRIBUTOR'S NAME : BTS INDUSTRIES

ADDRESS : 784 U.S. HIGHWAY 1, SUITE 4

NORTH PALM BEACH, FL 33408

A DIVISION OF HYDROSOL, INC.

EMERGENCY PHONE : 800-752-7869 DATE PRINTED : 5/8/2006

INFORMATION PHONE : 561-656-0850 NAME OF PREPARER : ESP

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS CAS NUMBER mm Hg @ TEMP PERCENT

* 2-BUTOXYETHANOL, GLYCOL ETHER EB 111-76-2 .6 68 5

OSHA PEL: 25 PPM, ACGIH TLV: 25 PPM.; SKIN

D-LIMONENE; 4-ISOPROPENYL-1-METHYLCYCLOHEXENE 5989-27-5 2 68 1

OSHA PEL: NOT ESTAB, ACGIH TLV: UNKNOWN

BUTANE 106-97-8 1640 68 3

OSHA PEL: 800 PPM, ACGIH TLV: 800 PPM

PROPANE 74-98-6 6350 68 1

OSHA PEL: 1000 PPM, ACGIH TLV: ASPHYXIA

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: -44 deg F - 336 deg F SPECIFIC GRAVITY (H2O=1): 0.96

VAPOR DENSITY: UNKNOWN EVAPORATION RATE: UNKNOWN

SOLUBILITY IN WATER: COMPLETE

APPEARANCE AND ODOR: AEROSOL PRODUCT

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: -156 deg F METHOD USED: ESTIMATED

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: .7 UPPER: 12.7

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES :WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP

AND EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED,

FOG NOZZLES PREFERRED. WEAR GOGGLES AND SELF-CONTAINED BREATHING APPARATUS. UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE FROM INTERNAL PRESSURE BUILD-UP WHEN EXPOSED TO EXTREME HEAT AND DISCHARGE CONTENTS. LIQUID CONTENT

OF CONTAINER WILL NOT SUPPORT COMBUSTION. OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE

READILY APPARENT. OBTAIN MEDICAL ATTENTION.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

APPLICATION TO HOT SURFACES. STORAGE ABOVE 120 DEG F. EXPOSURE TO OPEN FLAME.

INCOMPATIBILITY (MATERIALS TO AVOID)

OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

MAY PRODUCE FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBON MONOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

RESPIRATORY IRRITATION, HEADACHE, NAUSEA, FATIGUE, DROWSINESS, IMPAIRED CO-ORDINATION.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SKIN: SKIN MAY DRY THE SKIN; PROLONGED CONTACT MAY CAUSE IRRITATION. EYES: LIQUID OR VAPOR CAN IRRITATE. SKIN ABSORPTION HEALTH RISKS

AND SYMPTOMS OF EXPOSURE CAN BE ABSORBED. SOLVENT ACTION CAN DRY AND DEFAT THE SKIN CAUSING THE SKIN TO CRACK, LEADING TO DERMATITIS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

NOT A LIKELY ROUTE OF EXPOSURE. IF SWALLOWED, DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ADVICE AND/OR ATTENTION.

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE: EYE IRRITANT. SKIN IRRITANT. CHRONIC: UNKNOWN.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE NONE KNOWN.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR. ADMINISTER OXYGEN IF NEEDED. APPLY ARTIFICIAL

RESPIRATION IF BREATHING HAS STOPPED. GET MEDICAL ATTENTION. SKIN: WIPE OFF WITH TOWEL. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF

IRRITATION PERSISTS.

EYES: WASH IMMEDIATELY WITH LARGE VOLUMES OF FRESH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. CLEAN UP AREA WITH ABSORBENT MATERIAL AND PLACE IN CLOSED

CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. BEFORE ATTEMPTING CLEAN UP, REFER TO OTHER

SECTIONS OF THIS MSDS FOR HAZARD CAUTION INFORMATION.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE AND USE IN COOL, DRY, WELL-VENTILATED AREAS. DO NOT STORE ABOVE 120 DEG F.

DO NOT PUNCTURE OR INCINERATE (BURN) CANS. DO NOT STICK PIN, NAIL OR ANY OTHER

SHARP OBJECT INTO OPENING ON TOP OF CAN. DO NOT SPRAY IN EYES. DO NOT TAKE INTERNALLY. SEE PRODUCT LABEL FOR ADDITIONAL INFORMATION.

OTHER PRECAUTIONS

THE STORAGE OF NON-FLAMMABLE PRODUCTS WITH NON-FLAMMABLE OR FLAMMABLE

PRESSURIZING AGENT, IN CARTONS, IS THE SAME AS FOR ORDINARY CANNED GOODS IN CARTONS.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION: NONE UNDER NORMAL USE.

VENTILATION SUFFICIENT TO PREVENT INHALATION OF SOLVENT VAPORS. GENERAL DILUTION AND/OR

LOCAL EXHAUST VENTILATION IN VOLUME OR PATTERN TO KEEP PEL/TLV OF MOST HAZARDOUS INGREDIENT BELOW ACCEPTABLE LIMIT AND LEL BELOW

STATED LIMIT.

PROTECTIVE GLOVES: NONE UNDER NORMAL USE. SOLVENT RESISTANT REQUIRED FOR PROLONGED OR REPEATED CONTACT.

EYE PROTECTION: NONE UNDER NORMAL USE; HOWEVER, USE OF SAFETY GLASSES WITH SPLASH GUARDS OR FULL

FACE SHIELD IS RECOMMENDED.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NONE UNDER NORMAL USE; HOWEVER, USE OF SOLVENT RESISTANT APRONS OR OTHER

CLOTHING IS RECOMMENDED.

WORK/HYGIENIC PRACTICES

EYE WASHES AND SAFETY SHOWERS IN THE WORKPLACE ARE RECOMMENDED.

===== SECTION IX - DISCLAIMER =====

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BECAUSE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY FOR ITS USE.